

OPTIX[®]

FRAMING

Substrate Solutions



Plaskolite's line of picture frame glazing acrylic sheet offers a variety of advantages over glass. Half the weight of glass, 10-20 times more impact resistant, and unsurpassed optical clarity make OPTIX acrylic sheet the clear choice for a variety of framing applications.

OPTIX[®] FRAME GRADE

- Available in a thickness range from .060" to .118", 48" x 96" sheet size
- Non-stock thickness available from .060" to .236"
- Camera inspected throughout the manufacturing process
- Produced specifically for the picture frame industry

OPTIX[®] UVF

- Available in .098" and .118", 48" x 96" sheet size
- Non-stock thickness available from .060" to .236"
- Provides the highest protection from damaging UV light, absorbing 98% of the harmful rays
- Camera inspected throughout the manufacturing process

OPTIX[®] NON-GLARE

- Available with either a heavy or light matte finish
- Heavy matte available in a thickness range from .060" to .220", 48" x 96" sheet size
- Light matte available in a thickness range from .060" to .125", 48" x 96" sheet size
- Reduces unwanted glare and reflection from any viewing angle

PLASKOLITE, INC.

P.O. Box 1497 • Columbus, Ohio 43216
614-294-3281 • Fax: 877-538-0754
E-mail: plaskolite@plaskolite.com • www.plaskolite.com